


TFC Coaxial Cable Product Information Sheet Type: T10750J

750 Series Coaxial Cable Copper Clad Aluminum Conductor Foamed Polyethylene Dielectric Seamless Aluminum Tube Outer Conductor Medium Density Polyethylene Jacket



Cable Ordering Information

| Cable Claeling Informa | | | |
|---------------------------------|------------------------------|-------------------|--------|
| Part Number | Desc | NEC / CSA Listing | |
| 750750J000BK00100001 | T10750J | n/a | |
| | | | |
| Characteristics | | | |
| Material | Detail | inches | mm |
| Inner Conductor | Copper Clad Aluminum | 0.166 | 4.22 |
| Dielectric | Foamed Polyethylene | 0.678 | 17.2 |
| Outer Conductor | Seamless Aluminum Tube | 0.750 | 19.1 |
| Floodant | | | |
| Jacket | Polyethylene, Outdoor, Black | 0.820 | 20.8 |
| Messenger | | | |
| Cable Width | | | |
| Mechanical Specifications | | | |
| Minimum Bend Radius, in. (mm) | | 6.0 | (152) |
| Product Weight, lbs/kft (kg/km) | (less reel) | 208 | (310) |

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

 Document:
 t10750j_1ghz12.doc

 Revision:
 10.6.2014

 Page:
 1 of 2

uncontrolled copy All Rights Reserved, Specifications subject to change without notice
 Times Fiber Communications, Inc.

 358 Hall Avenue

 Wallingford, CT 06492

 Toll Free +1-800-677-2288

 Toll +1-434-432-1800

 Fax +1-434-432-1821

 www.timesfiber.com



TFC Coaxial Cable Product Information Sheet Type: T10750J

| Electrical Specifications | | | | | | |
|----------------------------|------------|-----------|--|--|--|--|
| Impedance, Ω | 75 ± 2 | | | | | |
| Velocity of Propagation, % | 87 | | | | | |
| Capacitance, Nominal | 15.6 pF/ft | 51.2 pF/m | | | | |
| DC Resistance | Ω / kft | Ω / km | | | | |
| Inner Conductor | 0.58 | 1.90 | | | | |
| Outer Conductor | 0.17 | 0.56 | | | | |
| Loop | 0.75 | 2.46 | | | | |

| Attenuation, Maximum @ 68 °F (20 °C) | | | | | | | |
|--------------------------------------|-------------|------------|--|--|--|--|--|
| Frequency, MHz | dB / 100 ft | dB / 100 m | | | | | |
| 5 | 0.11 | 0.36 | | | | | |
| 55 | 0.37 | 1.21 | | | | | |
| 211 | 0.73 | 2.41 | | | | | |
| 250 | 0.81 | 2.65 | | | | | |
| 270 | 0.84 | 2.76 | | | | | |
| | 0.89 | 2.92 | | | | | |
| 330 | 0.94 | 3.08 | | | | | |
| 350 | 0.97 | 3.18 | | | | | |
| 400 | 1.05 | 3.44 | | | | | |
| 450 | 1.12 | 3.67 | | | | | |
| 500 | 1.18 | 3.87 | | | | | |
| 550 | 1.25 | 4.10 | | | | | |
| 600 | 1.31 | 4.30 | | | | | |
| 750 | 1.48 | 4.86 | | | | | |
| 870 | 1.61 | 5.28 | | | | | |
| 1000 | 1.74 | 5.71 | | | | | |

| Notes: | | | |
|--------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

 Document:
 t10750j_1ghz12.doc

 Revision:
 10.6.2014

 Page:
 2 of 2

uncontrolled copy All Rights Reserved, Specifications subject to change without notice
 Times Fiber Communications, Inc.

 358 Hall Avenue

 Wallingford, CT 06492

 Toll Free +1-800-677-2288

 Toll +1-434-432-1800

 Fax +1-434-432-1821

 www.timesfiber.com